


Seating Configuration

CITYRIDE SKL 30+A+D LP 410/35



CITYRIDE SKL 40+A+D LP 710/43



Reliability and Uptime



Superior Service Network
5-year / 5 00 000 km driveline warranty*
3-year / 3 00 000 km
standard body warranty*



The Next Generation
Connected Vehicle Platform
for your fleet.



Annual Maintenance Contract
& Fleet Management Solutions
for your maintenance needs.

TATA MOTORS
COMMERCIAL VEHICLES

To know more, visit your nearest Tata Motors dealership

busesandvans.tatamotors.com

18 00 20 97 979 Follow us on    

All pictures shown are for illustration purpose only. Actual product may vary. CAUTION: Accessories shown in the picture or elsewhere do not constitute standard fitment. The specifications are merely indicative. Due to continuous product improvements, these specifications are liable to change without notice.

*Whichever is earlier.

TATA MOTORS | Better
COMMERCIAL VEHICLES Always



MORE VALUE. MORE MILES

Presenting Tata CityRide School Buses



29 Safety
Features

TATA KA BHAROSA

 Built for Safety |  Better Fuel Efficiency |  Lower TCO

TATA
CITYRIDE

KEY FEATURES

Comfort & Convenience



Parabolic Suspension for Passenger Comfort



Tilt and Telescopic Steering for Driver Comfort



Higher Saloon Space & Comfortable Seating Layout

Performance



Best-in-class Fuel Efficiency



Fire Alarm and Protection System (FAPS)



Enhanced Braking Efficiency for Safety

Technical Specifications

Bus	CITYRIDE SKL 30+A+D LP 410/35	CITYRIDE SKL 40+A+D LP 710/43
Bus Model	LP 410/35	LP 710/42
Wheelbase	3 500 mm	4 290 mm
Engine	TATA 4SP CR	TATA 4SP CR
Engine Power	74 kW @ 2 800 r/min	74 kW @ 2 800 r/min
Engine Torque	300 Nm @ 1 400 - 2 200 r/min	300 Nm @ 1 400 - 2 200 r/min
Clutch Diameter	280 mm	280 mm
Gearbox	GB400 - Cable Shift	GB400 - Cable Shift
Brakes	All Wheel H2LS	All Wheel H2LS
Suspension	Parabolic Suspension	Parabolic Suspension
Steering	Power Steering, Tilt - Telescope	Power Steering, Tilt - Telescope
Battery	12 V, 100 Ah	12 V, 100 Ah
Alternator	75 A	75 A
Tyres	7.50X16	7.50X16
Fuel Tank Capacity (Litres)	60 Metal	90 Metal
DEF Tank Capacity	18 L	18 L
Max. GVW	6 000 kg	6 900 kg
Seating Capacity	SKL: 30 & 24 STD: 24	SKL: 40 & 32 STD: 32
Length	6 960 mm	8 224 mm
Rear Overhang	2 100 mm	2 574 mm
Front Overhang	1 360 mm	1 360 mm
Overall Height	2 910 mm	2 910 mm
Max. Width	2 200 mm	2 200 mm
TCD	12 900 mm	16 200 mm
Ground clearance	180 mm	180 mm